

RF Power Splitter

EPS-708x



E-INSTRUMENT TECH LTD.



KEY FEATURES

- ▶ 700M~8GHz
- ▶ Max Power 5W
- ▶ SMA Type
- ▶ Low Loss and High Isolation
- ▶ Broadband Power dividers

E-INSTRUMENT TECH LTD.

TW Office: +886.3.457.6809 | CHINA Office: +86.755.8299.6514 / +86.512.5792.3166

www.e-channel.com.tw

EPS-708A

- ▶ Frequency Range 頻率範圍 : 700M~8 GHz
- ▶ **Port : 1 to 2**
- ▶ VSWR 駐波比 : <1.8@700M~1.5GHz
<1.2@1.5G~8GHz
- ▶ Isolation 隔離度 : 20dB
- ▶ Insertion : 3dB+0.5 @700MHz
@2.0 GHz
@5.8 GHz
@8.0 GHz
- ▶ Connector Type 接頭型式 : SMA
- ▶ Impedance 阻抗 : 50Ω
- ▶ Max Power 最大輸入功率 : 5W
- ▶ Dimensions 尺寸 : 40x10x25mm
- ▶ N.W 重量 : 12g

EPS-708C

- ▶ Frequency Range 頻率範圍 : 700M~8 GHz
- ▶ **Port : 1 to 4**
- ▶ VSWR 駐波比 : <2.3@700M~1GHz
<1.4@1G~8GHz
- ▶ Isolation 隔離度 : 20dB
- ▶ Insertion : 6dB+1 @700MHz
@2.0 GHz
@5.8 GHz
@8.0 GHz
- ▶ Connector Type 接頭型式 : SMA
- ▶ Impedance 阻抗 : 50Ω
- ▶ Max Power 最大輸入功率 : 5W
- ▶ Dimensions 尺寸 : 40x10x50mm
- ▶ N.W 重量 : 18g

EPS-708A Insertion Loss



EPS-708C Insertion Loss



* Other product please see www.e-channel.com.tw